

MORE FROM WOOD.




EGGER PRO Large Format Laminate Flooring



Large



Kingsize



2



4




32



20



8 mm



UNI fit!



Patented

EGGER PRO Large Format

EGGER PRO FLOORING

8/32 LARGE & KINGSIZE

TECHNICAL DATASHEET

COREBOARD	HDF Swell stopp plus
PROFILE	The patented UNI fit! installation system stands for quick and simple installation process without glue. Produced under the licence of Flooring Industries™
GUARANTEE DOMESTIC AREA	20 years according to Egger Guarantee
GUARANTEE COMMERCIAL AREA	5 years according to Egger Guarantee
ANTISTATIC PROPERTIES ACCORDING TO EN1815	Yes, <2 kV
CLASS USE	32

EUROPEAN NORM EN13329



BOARD INFORMATION	LARGE	KINGSIZE
FORMAT	Large	Kingsize
DIMENSIONS mm [length x width]	1291 x 246	1291 x 327
COMPLETE THICKNESS	8	8
BEVEL	WV4	Non V and WV2
<u>PACK INFORMATION</u>		
PIECES/PACK	8	6
m ²	2.54m ²	2.53m ²
Kg	19.04	18.31

CLASSIFICATION AND GENERAL REQUIREMENTS ACCORDING EN13329

ABRASION RESISTANCE ACCORDING EN13329, annex E	AC4(ip≥4000)
IMPACT RESISTANCE ACCORDING EN13329, annex H	Big ball: ≥ 750mm Small ball: ≥ 12 N
RESISTANCE TO STAINING EN438	Group 1 + 2: level 5 Group 3: level 4
EFFECT OF FURNITURE LEG ACCORDING TO EN424	No damage shall be visible, when tested with foot Type 0 artefact
EFFECT OF CASTOR CHAIR ACCORDING TO EN425 (Type W)	No change in appearance or damage
THICKNESS SWELLING ACCORDING TO ISO24336	≤181%
TOLERANCE OF TOP LAYER ACCORDING TO EN13329	Length ±0.5mm Width ±0.1mm Thickness ± 0.5mm
LIGHT FASTNESS ACCORDING EN13329	Grey scale ≥level 4(EN:20105-A02)
STATIC INDENTATION BY CONSTANT PRESSURE ACCORDING TO EN ISO 24343-1	<0.05
SURFACE SOUNDNESS ACCORDING EN13329, annex D	≥1,2 N/mm ²
THERMAL RESISTANCE ACCORDING TO EN12667	0.07m ² K/W

